

aa  
1. (Amended) A liquid crystal display which comprises a pair of substrates and a liquid crystal layer sandwiched between the pair of substrates;

wherein where the alignment state of a liquid crystal when no voltage is applied to the liquid crystal layer is defined as an alignment state 1 and the alignment state of the liquid crystal used for performing displaying is defined as an alignment state 2, the alignment state 1 differs from the alignment state 2;

wherein source wiring electrodes, gate wiring electrodes, and switching elements are disposed on one of the substrates;

wherein a flattening film is stacked on the switching elements;

wherein pixel electrodes electrically connected to the switching elements are disposed on the flattening film; and

wherein in plan view, the pixel electrodes overlap with the source wiring electrodes or the gate wiring electrodes.

2. (Amended) A liquid crystal display according to claim 1, wherein in plan view, the pixel electrodes overlap with the source wiring electrodes and the gate wiring electrodes.

a2  
Cont

3. (Amended) A liquid crystal display according to claim 1, wherein the flattening film is composed of a resin layer.

---

Cancel claim 4 without prejudice or disclaimer.

Amend claims 5 to 9 as follows:

---

1003426-12001

a3

5. (Amended) A liquid crystal display according to claim 1, wherein the alignment state 1 is a splay alignment state whereas the alignment state 2 is a bend alignment state.

6. (Amended) A liquid crystal display according to claim 1, wherein irregularities are provided on the flattening film, and the level differences of the irregularities are  $1\mu\text{m}$  or less.

7. (Amended) A liquid crystal display according to claim 6, wherein the level differences of the irregularities are  $0.5\mu\text{m}$  or less.

8. (Amended) A liquid crystal display according to claim 1,  
wherein the spacing between the pixel electrodes is within the  
range of from  $1\mu\text{m}$  to  $10\mu\text{m}$ .

9. (Amended) A liquid crystal display according to claim 1,  
wherein one of the substrates has a plurality of pixel electrodes  
and the spacing between the pixel electrodes is within the range of  
from  $1\mu\text{m}$  to  $5\mu\text{m}$ .

Cancel claims 12 to 32 without prejudice or disclaimer.

Amend claims 33, 34, 39 to 41, 45, 46, and 49 as follows:

33. (Amended) A liquid crystal display which comprises a pair  
of substrates having electrodes and a liquid crystal layer  
sandwiched between the pair of substrates,

wherein the liquid crystal layer is oriented in a splay  
alignment;

wherein alignment films are stacked on the electrodes; and

wherein by making the thickness of the alignment films themselves nonuniform, the surfaces of the alignment layers each have an irregular configuration.

Ad Cont. 34. (Amended) A liquid crystal display which comprises a pair of substrates having electrodes and a liquid crystal layer sandwiched between the pair of substrates,

wherein the liquid crystal layer is oriented in a splay alignment;

wherein alignment films are stacked on the electrodes; and

wherein by making the thickness of the electrodes nonuniform, the surfaces of the alignment layers each have an irregular configuration.

AS Sub 39. (Amended) A method of manufacturing a liquid crystal display which comprise a pair of substrates including electrodes and a liquid crystal layer sandwiched between the pair of substrates, wherein the liquid crystal layer is oriented in a splay alignment, and wherein the surfaces of alignment layers formed on the surfaces of the electrodes each have an irregular configuration,

the method comprising the step of forming the irregular configurations of the electrode surfaces by use of a UV asher, ozone asher, UV/ozone asher or the like.

40. (Amended) A method of manufacturing a liquid crystal display which has a pair of substrates having electrodes and a liquid crystal layer sandwiched between the pair of substrates;

wherein the liquid crystal layer is oriented in a splay alignment; and

wherein the surfaces of alignment layers formed on the surfaces of the electrodes each have an irregular configuration,

the method comprising:

a dispersion step of dispersing, beforehand, powder or minute particles into printing varnish used for forming the alignment layers on the surfaces of the electrodes; and

an alignment layer formation step of forming the alignment layers by applying the varnish onto the surfaces of the electrodes and baking the varnish.

45  
con

41. (Amended) A liquid crystal display which comprises a pair of substrates having electrodes and a splay-aligned liquid crystal layer sandwiched between the pair of substrates;

wherein a plurality of spacers are placed between the pair of substrates;

wherein the spacers are securely attached to at least either one of the substrates with an adhesive which increases the pretilt angle of liquid crystal molecules within the liquid crystal layer; and

wherein the adhesive is spread over the substrate.

1000346-12601

45. (Amended) A liquid crystal display according to Claim 41, wherein a voltage is applied across the electrodes to cause a transition of the liquid crystal layer from a splay alignment to a bend alignment, thereby performing displaying.

46. (Amended) A method of manufacturing a liquid crystal display which comprises a pair of substrates having electrodes and a splay-aligned liquid crystal layer sandwiched between the pair of substrates,

the method comprising:

a6  
cont

a spacer scattering step of scattering spacers onto at least either one of the pair of substrates, the spacers having an adhesive adhered thereto which increases the pretilt angle of liquid crystal molecules within the liquid crystal layer;

a substrate stationary placement step of placing the substrates so as to be stationary, over which the adhesive is allowed to spread; and

a liquid crystal cell formation step of forming a liquid crystal cell by sticking the pair of substrates together.

10003442601

a7 49. (Amended) A method of manufacturing a liquid crystal display which comprises a pair of substrates having electrodes and a splay-aligned liquid crystal layer sandwiched between the pair of substrates,

the method comprising:

a spacer scattering step of scattering spacers onto at least either one of the pair of substrates, the spacers having an adhesive adhered thereto which increases the pretilt angle of liquid crystal molecules within the liquid crystal layer; and

a substrate stationary placement step of sticking the pair of substrates together on which the adhesive is allowed to spread.